

Reedy 540-SL/550-SL/1515-SL Specifications

Model	540-SL 3300kV	540-SL 3900kV	540-SL 4900kV	540-SL 6100kV
Item No.	920	921	922	923
Cells	2-3 LiPo, 4-8 NiMH	2-3 LiPo, 4-8 NiMH	2 LiPo, 4-6 NiMH	2 LiPo, 4-6 NiMH
RPM/Volt	3300	3900	4900	6100
Diameter	36mm	36mm	36mm	36mm
Length	50mm	50mm	50mm	50mm
Weight	190g/6.7oz	190g/6.7oz	190g/6.7oz	190g/6.7oz
Shaft Diameter	3.17mm	3.17mm	3.17mm	3.17mm
Max. Efficiency Current	10~40A	10~45A	10~50A	10~55A
Max. Surge Current	45A/60s	50A/60s	55A/60s	60A/60s
Internal Resistance	20mΩ	16mΩ	12mΩ	8mΩ

Model	550-SL 3500kV	550-SL 4000kV	1515-SL 2000kV
Item No.	924	925	929
Cells	2-3 LiPo, 4-8 NiMH	2-3 LiPo, 4-8 NiMH	3-4 LiPo
RPM/Volt	3500	4000	2000
Diameter	36mm	36mm	40mm
Length	55mm	55mm	74mm
Weight	210g/7.4oz	200g/7.1oz	380g/13.4oz
Shaft Diameter	5.0mm	5.0mm	5.0mm
Max. Efficiency Current	10~45A	10~50A	20~50A
Max. Surge Current	55A/60S	60A/60S	100A/15s
Internal Resistance	6.5mΩ	6.2mΩ	6.2mΩ